DINGLI · MODEL BA16NE / BA18CERT2

Dingli 16m & 18m Articulating Boom Lifts

Electric articulating booms: compact 1.73 m wide 16m BA16NE for tight indoor sites, or 18m BA18CERT2 with 9.45 m outreach and 4WD. Zero emission.



BEST FOR

- Data centre fit-out and cable tray work
- Indoor work in factories, warehouses, malls and data halls
- Tight sites and narrow access routes (16m BA16NE)
- Reaching up and over pipework, plant or machinery
- Cladding and roof sheeting on industrial buildings (18m BA18CERT2)
- High-bay lighting and M&E installation

Key specifications

Working height	16.3 m (BA16NE) / 18.1 m (BA18CERT2)
Platform height	14.3 m (BA16NE) / 16.1 m (BA18CERT2)
Max horizontal outreach	7.75 m (BA16NE) / 9.45 m with 1.5 m jib (BA18CERT2)
Platform capacity	230 kg (BA16NE) / 320 kg (BA18CERT2)
Power	48 V battery, zero emission (BA18CERT2: 48 V / 375 Ah)
Drive	Two-wheel drive (BA16NE) / 4WD positive traction, rough terrain capable (BA18CERT2)
Width and tyres	BA16NE: 1.73 m wide, non-marking foam-filled tyres
BA18CERT2 platform size	1.83 x 0.79 m

Daily, weekly or monthly rental · Also for sale · Delivery across Johor, KL & Selangor · Operator training available on site or at our Johor yard · Rates on enquiry.

Specifications are indicative and may vary by unit. Updated Nov 2026.

A&G Equipment Sdn. Bhd.
No. 9, Jalan SILC 2/3, Kawasan Perindustrian SILC, 79200 Iskandar Puteri, Johor
WhatsApp 012-308 9666 · Office 07-509 5663 · sales.my@angeqmt.com · angequipment.com.my