MERLO · MODEL TELEHANDLER RANGE

Merlo Telehandlers

Merlo telehandlers from the compact TF33.7 to the 360° Roto 50.26, lifting up to 12,000 kg or up to 26 m for construction and industrial sites.



BEST FOR

- Supplying blocks, rebar, formwork and roofing materials on construction sites
- Multi-storey, roofing and facade work
- Steel erection and placing loads well inside the building line
- Petrochemical and industrial maintenance and shutdowns
- Agriculture and plantations
- Ports, project cargo and outdoor yard work

Key specifications

Turbofarmer TF33.7 (compact)	3,300 kg, 7 m lift height, 3.5 m outreach, 115 hp
Panoramic P40.17 (stabilised)	4,000 kg, 17 m lift height, 12.5 m outreach
Panoramic P72.10 (high capacity)	7,200 kg, 10 m lift height
Panoramic P120.10 (high capacity)	12,000 kg, 10 m lift height, 170 hp
Roto 50.26 (360° rotating)	5,000 kg, 26 m lift height, 22.9 m outreach

Daily, weekly or monthly rental · Also for sale · Delivery across Johor, KL & Selangor · Operator training available on site or at our Johor yard · Rates on enquiry.

Specifications are indicative and may vary by unit. Updated Nov 2026.

A&G Equipment Sdn. Bhd.
No. 9, Jalan SILC 2/3, Kawasan Perindustrian SILC, 79200 Iskandar Puteri, Johor
WhatsApp 012-308 9666 · Office 07-509 5663 · sales.my@angeqmt.com · angequipment.com.my